



Submitted Model No.:


# **Specific Features:**







# RP54752▲ 1.5 GPM H<sub>2</sub>O Showerhead 4 1/2" (114 mm) Full Spray 3 7/8" (98 mm)



# ▲ Designate Proper Finish Suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.specselect.com for finish options and product availability.

# **O**DELTA

# TUB AND SHOWER FAUCET TRIM

- Linden<sup>™</sup> Bath Collection
- Valve Only (T14094)
- Tub Only (T14194)
- Shower Only (T14294 & T14294-H20)
- Tub/Shower (T14494 & T14494-H20)

### **STANDARD SPECIFICATIONS:**

- Monitor<sup>®</sup> 14 Series pressure balanced bath mixing valve with Scald-Guard<sup>®</sup>.
- Maintains a balanced pressure of hot and cold water even when a valve is turned on or off elsewhere in the system.
- For use with MultiChoice<sup>®</sup> Universal rough valve body. (R10000 Series)
- Back-to-back installation capability.
- Solid brass forged body.
- Temperature only controlled with handle.
- Field adjustable to limit handle rotation into hot water zone.
- 120° maximum handle rotation.
- All parts replaceable from the front of the valve.
- H<sub>2</sub>O Kinetic Technology® 1.5 gpm max @ 80 PSI.

## **WARRANTY**

- Lifetime Faucet and Finish Limited Warranty to the original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all industrial, commercial and business applications.








# **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
- ASSE 1016
- Indicates compliance to
- ICC/ANSI A117.1
- Indicated models meet EPA WaterSense





55 E. 111th Street, Indianapolis, Indiana 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2011 Masco Corporation of Indiana